



SHANDONG HOSEA CHEMICAL CO.,LTD..

Add: No A1303, Five-star building, Shouguang, Shandong, China

Website: www.hoseachemical.com E-mail: info@hoseachem.com

Tel: +86-536-8662448 Fax: +86-536-8050502

Technical Data Sheet (TDS)

Specification of Product

Product Name : Sodium Carboxymethyl Cellulose

Grade : 8207

Packing : 25Kg net composite kraft paper bag with PE inner

Storage and Shelf-life : 24month under cool and dry condition

Application:

Use as thickener, emulsifier in water-based paints, glue, adhesive etc.

Item	Range
Exterior	White and Yellowish powder
Viscosity(1% mPa.s)	1500-1800
D.S	≥0.7min
Purity, %	≥99.5%
PH Value 1%	6.0-8.5
Moisture Content	≤ 10.0max
Heavy metal(Pb),%	≤ 2ppm
Iron(Fe),%	≤ 80ppm
Arsenic(As),%	≤ 2ppm
Cu & Zn, %	≤ 50ppm
Mercury, Hg, %	≤ 0.5ppm
Cadmium, %	<1 ppm
Particle size (sieving)	≥95% (pass through 100 mesh)

Viscosity measured on dry basis of 1% water solution, at 25 Deg C, Brookfield Viscometer, #4 spindle, 30rpm.